

Appendix A Specifications

General Specifications

Media Access	10Base-T and 100Base-TX.
Cable Tests	Length, wiremap, and split pairs.
Ports	Shielded Hub/NIC connector (RJ-45). Shielded Wiremap connector (RJ-45). RS-232C PC/Printer port (DB-9).
Printers Supported	HP LaserJet series.
Interface	Icon-based touchscreen display.

Battery	Removable/rechargeable NiMH battery, 2-hour life.
Dimensions	20.3 cm x 10.7 cm x 5.3 cm (8 in x 4.2 in x 2.1 in).
Weight	0.7 kg (1.7 lbs).
Warranty	One year. (Extended warranty available).
LED Indicators (5)	Link, Utilization, Collision, Error, and Battery Charge.
Toner Frequencies	Low: between 185 Hz and 200 Hz. High: between 350 Hz and 375 Hz.

Environmental Requirements

Operating Temperature 10°C to 30°C with up to 95% Relative Humidity
10°C to 40°C with up to 75% Relative Humidity

Non-Operating Temperature -20°C to +60°C

Approvals The Universal AC Adapter for the Network Assistant has UL, CSA, and TÜV approvals or other approvals valid in the USA, Canada, and Europe.

Electromagnetic Interference The Fluke OneTouch Network Assistant complies with German Law Vfg. 243.1991 when it is operated at least 28 meters from the boundary of the user's facility or in a screen room. Exempt for USA and Canadian emissions regulations if it does not interfere with licensed communications.

Certifications **CE**

Connection to public telephone network The Network Assistant should never be connected to the public telephone network.