

Resistive Voltage Dividers

...for the measurement of high voltages
using a standard digital voltmeter*

Spellman's HVD Series of high voltage dividers provide laboratory or production facilities with a convenient method of measuring up to 100kVdc, 200kVdc or 400kVdc with accuracy better than 0.5%. These dividers are designed for use with high impedance digital voltmeters. All HVD dividers are housed in a Plexiglas cylinder containing a matched set of precision metal film resistors which have a temperature coefficient of less than 25 ppm. A ladder-type construction technique is used in conjunction with polished high voltage bushings specifically designed to minimize corona. BNC connectors are used to provide the low voltage proportional output signal.

*Impedance of 10Gohm or higher.

WARNING

DANGEROUS LIFE THREATENING VOLTAGES MAY BE PRESENT ON THIS EQUIPMENT. OBSERVE EXTREME CAUTION WHEN OPERATING OR WORKING NEAR HIGH VOLTAGE DEVICES. NEVER TOUCH ANY HIGH VOLTAGE ASSEMBLY THAT IS SUSPECTED TO BE ENERGIZED OR CHARGED. DO NOT HANDLE OR COME WITHIN THE PROXIMITY OF HIGH VOLTAGE CONNECTIONS UNTIL ALL EQUIPMENT IS TURNED OFF AND THE SETUPS CAPACITANCE IS DISCHARGED. FAILURE TO FOLLOW SAFETY PROCEDURES MAY BE FATAL.



- **HIGH INPUT IMPEDANCE**
- **25PPM TEMPERATURE COEFFICIENT**
- **100KV, 200KV AND 400KV MODELS**
- **CORONA FREE OPERATION**
- **0.5% ACCURACY**
(HIGHER ACCURACIES AVAILABLE)

HVD

	HVD100	HVD200	HVD400
Input Voltage	0-100kVdc	0-200kVdc	0-400kVdc
Input Impedance	1000Mohms	2000Mohms	4000Mohms
Output Impedance	1M; 100kohms	20kohms	40kohms
Output Taps	100V, 10V	2V	4V
Accuracy	0.5%: (0.1% opt) ¹	0.5%: (0.25% opt) ²	0.5%: (0.25% opt) ²
Stability	0.01%/8hrs	0.025%/8hrs	0.025%/8hrs
Temp. Coefficient	25ppm/°C	25ppm/°C	25ppm/°C
Height	17.5" (44.5cm)	33.5" (84.5cm)	61" (154.94cm)
Max. Diameter	10" (25.4cm)	12" (30.5cm)	20" (50.8cm)
Weight	6.75 lbs (3.1kg)	12 lbs (5.5kg)	24.45 lbs (11.8kg)
Output Connector	BNC type	BNC type	BNC type

(1) For accuracy of 0.1% specify HVD100-1

(2) For accuracy of 0.25% specify HVD200-1 or HVD400-1



USA +1-631-630-3000
UK +44 (0)1798 877000
JAPAN +81 (0)48-447-6500
CHINA +86 (0)512-67630010

FAX: +1-631-435-1620
FAX: +44 (0)1798 872479
FAX: +81 (0)48-447-6501
FAX: +86 (0)512-67630030

e-mail: sales@spellmanhv.com
www.spellmanhv.com

128055-001 REV.C

Spellman High Voltage is an ISO 9001:2000 and ISO 14001:2004 registered company