

## Supports

Chipset: Alcatel Microelectronics

## SPECIFICATIONS

### ATU-R Function

Modem Status Measurements

- Link turn-up and live results
- Fastpath rate: Upstream and Downstream
- Interleaved bit rate: Upstream and Downstream
- Maximum bit rate: Upstream and Downstream
- Relative Capacity: Upstream and Downstream
- Noise Margin: Upstream and Downstream
- Attenuation: Upstream and Downstream
- Output Power: Upstream and Downstream

Alarm Status: Current and history results for Loss of Signal, Loss of Frame, Loss of Power, Loss of Cell Delineation Interleaved, Loss of Cell Delineation Fast, Loss of Margin

Link Measurements: Separate results for ATU-C/ATU-R and Interleaved/Fast FEC, CRC, and HEC measurements; block error rate, ES, SES, and UAS

Bits per Tone: Graphical and tabular display


PING Test

Protocols Supported

- RFC 1483: LLC-bridged (static & dynamic [DHCP]) and LLC-routed
- RFC 2364: PPP over ATM
- RFC 2516: PPP over Ethernet

### ATU-R Mode

- One-button turn-up test to sync with ATU-C/DSLAM
- Read modem status measurements, including current and max rate, noise margin for upstream and downstream
- Alarm and link measurements
- PING test
- Supports ANSI T1.413 Issue 2, ITU-T G.992.1 (G.DMT), and ITU-T G.992.2 (G.lite) modes



### Connectors

Line Interface: RJ45 @ 100Ω

### General

Module Size: 12.6 cm (W) x 9 cm (L) x 2.2 cm (H)  
[5.0" x 3.5" x 0.9"]

Operating Temperature: 0°C to 50°C [32°F to 122°F]

Storage Temperature: -20°C to 70°C [-4°F to 158°F]

Humidity: 5% to 85% noncondensing



The ATU-R Module is part of a family of Plug-In Modules for the SunSet xDSL Modular test set

## ORDERING INFORMATION

SSxDSL-3 Alcatel ADSL ATU-R Module  
CLEI: VATSDGABAA  
CPR: 774236

SWxDSL-3A PING Package for SSxDSL-3  
ICMP PING with ATM encapsulation to verify end-to-end provisioning. Requires Alcatel ATU-R Modem (SSxDSL-3)

### Recommended Cables

- SS161 Cable, RJ-45 (m) to 3 Probe Clips, 2 m
- SS162 Cross Cable, RJ-45 (m) 8-pin Modular Plug to RJ-14 6-pin Modular Plug, 2 m. Used for SunSet to Alcatel splitter's 6-position modem jack. (North America)
- SS167 Cable, RJ-45 (m) to RJ-45 (m), 2 m with Ferrite Filter
- SS168 Cable, RJ-45 (m) to RJ-11 (m), 2 m with Ferrite Filter

... a step ahead

22 Great Oaks Blvd.  
San Jose, CA 95119  
ph 1 408 363 8000  
fax 1 408 363 8313

info@sunrisetelecom.com

www.sunrisetelecom.com



Note: Specifications subject to change without notice.  
© 2001 Sunrise Telecom Incorporated. All rights reserved.  
Printed in USA.