## FC 200 Series CE

## There's a better solution... at a better price.



CE

## The FC 200 Series frequency and voltage converters are economically priced and offer top of the line performance.

The series consists of two 1 phase output instruments in sizes of 500VA and 1kVA. The converters allow the user to duplicate a utility grid of either 50 or 60 hertz for export product testing or operation of imported equipment. The frequency can also be adjusted to 400 hertz for applications such as the testing of military/avionics equipment or for the operation of 400 hertz electronics that are onboard an aircraft or a military vessel. The adjustable frequency band of 45 to 500 Hertz in conjunction with the dual voltage ranges of 0-150 volts or 0-300 volts provides full capabilities for testing and operating electronics worldwide.

Setup and operation of the FC 200 Series is exceptionally easy. The simple front panel layout allows users to continuously vary voltage and frequency or to select preset standard frequency settings. Individual meter displays provide digital readouts for frequency, voltage and current while a digital multimeter displays power or power factor.

The FC 200 Series converters are a simple and cost effective solution for all of your AC power conversion needs!

Key Features & Specifications for the FC 200 Series

- Output Power: 500VA and 1kVA (for larger 1-phase sizes up to 40kVA see the APS 1000 Series)
- Output Frequency: 45-500Hz
- Output Voltage: Dual range, 0-150V or 0-300V, 1 phase
- Isolated Output, THD: < 0.5%</li>
- Input Requirements: 115/230VAC ± 15%, 1 phase, 47-63Hz
- Intuitive Front Panel Controls: Frequency, Voltage and Current Limit
- Easy to Read LED Displays: Frequency, Voltage,
   Current and Power or Power Factor
- Memory Locations: Can save three desired settings of any voltage, frequency and current limit covered in the output parameters
- Power Outlets: Universal, Domestic and International Connectors
- Option: PLC Remote Interface which includes 7 memory locations
- Regulatory: CE Mark

Worldwide Supplier of Power Conversion Equipment ADAPTIVE POWER SYSTEMS

## FC 200 Series CE





MODEL		FC205	FC210
INPUT SPECIFICATIONS			
Input Phase		1-phase / 2-wire + Ground	
Input Voltage		115/230Vac ± 15%	
OUTPUT SPECIFICATIONS			
Power rating		500VA	1000VA
Max Arms @	0-150V	4.2A	8.4A
Max Arms @	0-300V	2.1A	4.2A
Phase		1-phase / 2-wire + Ground	
Voltage (r.m.s.)	Low Range	0-150V	
	High Range	0-300V	
	Resolution	0.1V	
	Accuracy	± (0.5% of setting+2 counts)	
Frequency	Range	45 - 500Hz	
	Resolution	0.1Hz at 45 - 99.9Hz, 1Hz at 100 - 500Hz	
	Accuracy	± 0.2%	
Harmonic Distortion		≤ 0.5% (Resistive Load)	
Crest Factor		≥ 4 to 1	
Load Regulation		± 0.5% (Resistive Load)	
Protection		Over-Current, Short-Circuit, Over-Temperature	
Operating Temperature		32°F - 104°F (0°C - 40°C), 80% Relative Humidity	
Altitude		Below 6,500 feet	
DISPLAY AND CONTROLS			
4 Digital LED meters		Frequency, Voltage, Current, Power or Power Factor (simultaneously)	
Memory (Standard)		3 Memories, 3 Programmable Parameters per Memory for: Voltage, Frequency, Current Limit	
Calibration		Front Panel Calibration	
REGULATORY COMPLIANCE		TOTAL AIRCI CAIK	
Approvals		CE Mark	
MECHANICAL SPECIFICATIONS			
Power Rating		500VA	1000VA
Dimensions (In / mm) H/D/W		3.5 x 16 x 17 / 89 x 406 x 431	3.5 x 22 x 17 / 89 x 559 x 431
Weight kg/lb		22/48	37/81



17711 Mitchell North, Irvine, CA 92614

Direct: 949-752-8400 • Fax: 949-756-0838

Toll Free US only: 1-866-517-8400

www.adaptivepower.com