



Site Analyzer XT Series

SA-3600XT, SA-6000XT



The RF Experts

- One unit covers the entire 25-6000 MHz range!
- Easy to operate and field ready for first-time, occasional and experienced users.
- Other applications include 3G, Broadcast, Government, Tactical Military, Microwave, Paging, Public Safety, Trunking, WLAN and WLL, and TETRA.
- Color display is clearly visible in direct sunlight.
- With a single download you can view data as Distance to Fault or Measurement Match-no need to store two traces.
- FDR (Frequency Domain Reflectometry) measurement method results in a highly reliable assessment of the health of critical components in your system; ultimately providing a “heads-up” before a failure occurs.
- Fault location or DTF mode indicates VSWR or Return Loss levels at each point along the cable and antenna system length.
- Cable Loss function measures insertion loss of the cable system over a given frequency range.
- USB communication ports for connection to PC, field sensors and storage devices.

APPLICATIONS

Suitable for use in Worldwide Cellular and PCS/DCS systems; supporting measurement of CDMA, GSM, TDMA and AMPS modulation schemes.

Other applications include 3G, Broadcast, Government, Tactical Military, Microwave, Paging, Public Safety, Trunking, WLAN and WLL, and TETRA.

SiteAnalyzer XT Series

SA-3600XT, SA-6000XT

SPECIFICATIONS

Frequency Range	SA-3600XT SA-6000XT	25-3600 MHz 25-6000 MHz
Frequency Resolution	SA-3600XT SA-6000XT	25 kHz; 25-800 MHz, 50 kHz; 800-2500 MHz, 150 kHz; 2500-3600 MHz 25 kHz; 25-800 MHz, 50 kHz; 800-2500 MHz, 150 kHz; 2500-6000 MHz
Power Measurement	SA-3600XT SA-6000XT	Yes Yes
Return Loss		0 to -60 dB
Test Port		N-type female connector
Impedance		50 ohms
Speed		1 multi-frequency scan (238 points)/2 seconds 1 multi-frequency scan (475 points)/3.5 seconds 1 multi-frequency scan (949 points)/6 seconds
Trace Resolution		238 (default), 475, or 949 per trace
Storage Capacity		Thousands of setups and traces
Immunity to Interfering Signals		Rejects on-frequency signals up to +13 dBm
Maximum Input Signal		+22 dBm
Data Transfer		Sensor: USB 2.0 Type A PC: USB 2.0 Type B
Internal Time		Rechargeable lithium-Ion batteries. 5-hour minimum operating time. Auto shut-off conserves battery life
External DC		9-15 VDC fused, <3 A
External AC		100 to 240 VAC @ 50-60 Hz; AC/DC adapter required
Operating Temperature		-10° to +50° C (+14° to +122° F)
Storage Temperature		-40° to +80° C (-40° to +176° F)
Battery Charging Temperature		0° to + 35° C (32° to 95° F)
Humidity		95% ± 5% max., (non-condensing)
Altitude		Up to 15,000 feet (4572 m)
Dimensions		10.5" x 8.4" x 3.3" (265 x 212 x 83 mm)
Weight		5.5 lbs. (2,5 kg)
Upgradeable		Yes, SA-3600XT maybe upgrade to SA-6000XT

STANDARD ACCESSORIES

AC Adapter (15 Vdc Output)	5B2229-1224G-1
Automobile Cigarette Lighter Adapter	5A2238-2
Soft Carrying Case	7002A850
USB Interface Cable	5A2653-10
PC Interface Software Kit	7002A840
Instruction Manual	920-SA-XT
Internal Battery Pack, with 4-pin Connector	5C2431-2

OPTIONAL ACCESSORIES

CAL-MN-C	Calibration Combo, (M) N
CAL-FN-C	Calibration Combo, (F) N
CAL-ME-C	Calibration Combo, (M) 7/16 DIN
CAL-FE-C	Calibration Combo, (F) 7/16 DIN
5012D	Wideband Power Sensor 350 MHz -4000 MHz
5014	Directional Power Sensor 2 - 2700 MHz
5015	Terminating Power Sensor 40 MHz - 4000 MHz
5015EF	Terminating Power Sensor 40 MHz - 12 GHz
5016D	Wideband Power Sensor 350 MHz - 4000 MHz
5017D	Wideband Power Sensor 25 MHz - 1000 MHz
5018D	Wideband Power Sensor 150 MHz - 4000 MHz
5019D	Wideband Power Sensor 25 MHz - 1000 MHz
7020-1-0101	Power Sensor 350 MHz - 4000 MHz
TC-MNMN-1.5	Test Cable, 1.5 m., N (M) conn.
TC-MNMN-3.0	Test Cable, 3 m., N (M) conn.
TC-MNFN-1.5	Test Cable, 1.5 m., N (M)/N (F) conn.
TC-MNFN-3.0	Test Cable, 3 m., N (M)/N (F) conn.
TC-MNME-1.5	Test Cable, 1.5 m., N (M) - 7/16 DIN (M)
TC-MNME-3.0	Test Cable, 3 m., N (M) - 7/16 DIN (M)
TC-MNFE-1.5	Test Cable, 1.5 m., N (M) - 7/16 DIN (F) conn.
TC-MNFE-3.0	Test Cable, 3 m., N (M) - 7/16 DIN (F) conn.
PA-MNME	Adapter, N (M) to 7/16 DIN (M)
PA-FNME	Adapter, N (F) to 7/16 DIN (M)
PA-MNFE	Adapter, N (M) to 7/16 DIN (F)
PA-FNFE	Adapter, N (F) to 7/16 DIN (F)
4240-550	Precision Connector Adapter Kit, 7/16 DIN, SA -Series
7002C870	Hard Shell Transit Case
RPK5C2431-2	Battery, Spare

