

Arbitrary Function Generators

▶ AFG310 • AFG320



▶ AFG300 Series.

AFG300 Series Delivers Five Functions in One Tool

Function Generator

The AFG300 Series is an excellent 16 MHz function generator with built-in arbitrary waveform, burst, sweep, and modulation capabilities. The instruments support standard waveforms including sine, square, triangle, ramp, pulse, DC and noise. Its sweep function includes Linear and Logarithmic (up or down) while operating in the Continuous, Triggered, and Burst modes.

Arbitrary Waveform Generation

With a sample rate of 16 MS/s, 12-Bit vertical resolution and a non-volatile memory that holds four 16,384-point waveforms, the AFG300 Series are powerful tools for simulating complex waveforms. Waveforms can be downloaded directly from selected Tektronix oscilloscopes and arbitrary waveform generators via GPIB, created with the standard ArbExpress waveform editing software package, or entered via the front panel.

▶ Features & Benefits

- Five Functions in One Instrument
- Function Generator
 - Arbitrary Waveform Generator
 - Burst Generator
 - Sweep Generator
 - Modulation Source

AFG320 Offers Two Independent Channels

Load Waveforms Directly from Selected Tektronix Digital Oscilloscopes via the GPIB Interface

Windows-based ArbExpress™ Waveform Editing Software Package Included for Convenient Creation and Editing of Arbitrary Waveforms

All Functions Including Waveform Creation and Editing Accessible via the Front Panel

Optional Rackmount Kit for System Applications

▶ Applications

- Design and Test
- Automotive
- Education
- Industrial
- Biomedical
- Sensor Simulation
- Manufacturing Test

COMPUTING

COMMUNICATIONS

VIDEO

Arbitrary Function Generators

► AFG310 • AFG320

► Characteristics

Output Channels –

AFG310: 1.

AFG320: 2.

Standard Waveforms – Sine, Square, Triangle, Ramp, Pulse, DC and Noise.

User Waveforms – (Preprogrammed samples)

USR1: Sin (X)/X.

USR2: Double Exponential Pulse.

USR3: Damped Sine Wave.

USR4: NRZ Random Signal.

Arbitrary Waveforms –

Waveform Length: 10 to 16384 points.

Vertical Resolution: 12-Bit.

Sample Rate: 16 MS/s.

Nonvolatile Memory: Four 16 k waveforms.

Output Frequency –

Sine, Square: 0.01 Hz to 16 MHz.

Triangle, Ramp, Pulse: 0.01 Hz to 100 kHz.

Noise (Gaussian): Maximum 8 MHz bandwidth.

Arbitrary Waveform:

Repetition Rate: 0.01 Hz to 1.6 MHz.

Resolution: 7 digits.

Accuracy: 50 ppm.

Output Characteristics –

Amplitude (into 50 Ω): 50 mV_{p-p} to 10 V_{p-p}.

Accuracy: $\pm(1\%$ of setting + 5 mV) at 1 kHz, no offset.

Flatness (at 1 V amplitude relative to 1 kHz):

<100 kHz: $\pm 1\%$.

100 kHz to 1 MHz: $\pm 1.5\%$.

1 MHz to 16 MHz: $\pm 3\%$.

Offset (into 50 Ω):

505 mV_{p-p} to 10 V_{p-p} amplitude: peak amplitude + offset is limited to +5 V or –5 V.

50 mV_{p-p} to 500 mV_{p-p} amplitude: –0.75 V to +0.75 V.

Accuracy: $\pm(1\%$ of setting +5 mV).

Resolution: 5 mV.

Output Impedance: 50 Ω .

Isolation: 42 V peak maximum relative to earth ground.

Phase:

Range: $\pm 360^\circ$.

Resolution: 1° .

Sine Wave Spectral Purity –

Harmonic Distortion:

DC to 20 kHz: –65 dBc.

20 kHz to 100 kHz: –60 dBc.

100 kHz to 1 MHz: –45 dBc.

1 MHz to 16 MHz: –35 dBc.

Total Harmonic Distortion:

20 kHz: 0.05% at 1 V amplitude.

Signal Characteristics –

Square:

Rise/Fall Time: ≤ 20 ns.

Overshoot: $\ll 2\%$.

Pulse:

Rise/Fall Time: $\ll 100$ ns.

Duty Cycle: 1% to 99% of period.

Triangle, Ramp, Pulse, Arbitrary:

Jitter: 2 ns at 100 kHz.

Modulation –

AM:

Source: External only.

Carrier: Up to 16 MHz.

Modulation: Any internal waveform plus Arb.

Frequency: DC to 200 kHz.

Depth:

1 V: 100%.

0 V: 50%.

–1 V: 0%.

2 V_{p-p} for 100% modulation.

FM:

Source: Internal only.

Modulation: Sine, Square, Triangle, Arb.

Frequency: 0.01 Hz to 10 kHz.

Deviation: 0.01 Hz to 8 MHz.

FSK (frequency shift keying):

Source: Internal only.

Mode: Trigger, Burst.

Frequency Range: 0.01 Hz to 16 MHz.

Key Rate: 0.01 Hz to 50 kHz.

Number of Keys: 2.

Frequency Sweep –

Type: Linear or logarithmic.
 Direction: Up or down.
 Start/Stop Frequency: 0.01 Hz to 16 MHz.
 Time: 1 ms to 100 s.
 Mode: Continuous, Trigger, Burst.

Operating Mode –

Continuous: The selected waveform is output continuously.
 Triggered: One period of the selected waveform is output each time a trigger occurs.
 Trigger source: Manual, external.
 Burst: The selected waveform is output with a specified number of cycles each time a trigger occurs.
 Carrier Frequency: Up to 1 MHz.
 Count: 1 to 60,000 cycles/burst (100 s maximum except sine wave or square wave) or infinite.
 Start phase: –360 to +360°.
 Trigger Source: Manual, external.

Inputs/Outputs –

Front Panel:
 Main Output: Ch 1, Ch 2 (AFG320 only).
 External Trigger (Burst) Input:
 TTL input.
 Pulse-width: 1 μ s minimum.
 10 k Ω input impedance.
 Rear Panel:
 Sync Output: TTL level.
 External AM Modulation:
 2 V_{p-p} = 100% modulation.
 10 k Ω input impedance.
 GPIB Interface (IEEE-488.2).

Memory –

Type: Non-volatile.
 Setup Storage: 20.
 Arbitrary Waveform Storage: 4.

Environmental, EMC, Safety

Temperature Range –

Operating: 0 °C to +50 °C.
 Nonoperating: –20 °C to +60 °C.

Humidity –

Operating:
 At or below +40 °C: 0 to 95%.
 +40 °C to +50 °C: 0 to 75%.

Random Vibration –

Operating: 0.31 G_{RMS} from 5 to 500 Hz, 10 minutes.
 Nonoperating: 2.46 G_{RMS} from 5 to 500 Hz, 10 minutes.

Shock –

Nonoperating: 294 m/s² (30 G), half-sine, 11 ms duration.

EMC Compliance –

Meets intent of Directive 89/396/EEC for Electromagnetic Compatibility.
 Australian AN/NZS 2064.1/2.

Safety –

UL1244, CSA231, EN61010-1, IEC61010-1.

Power

Line Voltage –

90 to 132 V AC, 180 to 250 V AC.

Line Frequency –

90 to 250 V: 48 to 63 Hz.
 90 to 127 V: 48 to 440 Hz.

Physical

Characteristics

Dimensions	mm	in.
Height	99	3.9
Width	214	8.4
Depth	411	16.2
Weight	kg	lbs.
Net: AFG310	5.4	11.9
Net: AFG320	5.6	12.3

► Ordering Information

AFG310

Single-channel Programmable Arbitrary Function Generator.

AFG320

Dual-channel Programmable Arbitrary Function Generator.

Includes: User manual, Calibration Certificate, power cord, ArbExpress Software.

Please specify power plug when ordering.

Recommended Accessories

Rackmount Kit – Order 016-1674-00.

Power Plug Options

Opt. A0 – North America Power.

Opt. A1 – Universal EURO Power.

Opt. A2 – United Kingdom Power.

Opt. A3 – Australia Power.

Opt. A4 – 240 V, North America Power.

Opt. A5 – Switzerland Power.

Service

Tektronix CAL and REP Service programs allow you to pre-purchase genuine Return to Tektronix Service. Ask your Distributor for details.

Opt. C3 – Calibration Service 3 Years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years (with Option C3).

Warranty

Three years parts and labor.

Arbitrary Function Generators

▶ AFG310 • AFG320

Contact Tektronix:

ASEAN / Australasia / Pakistan (65) 6356 3900

Austria +43 2236 8092 262

Belgium +32 (2) 715 89 70

Brazil & South America 55 (11) 3741-8360

Canada 1 (800) 661-5625

Central Europe & Greece +43 2236 8092 301

Denmark +45 44 850 700

Finland +358 (9) 4783 400

France & North Africa +33 (0) 1 69 86 80 34

Germany +49 (221) 94 77 400

Hong Kong (852) 2585-6688

India (91) 80-22275577

Italy +39 (02) 25086 1

Japan 81 (3) 6714-3010

Mexico, Central America & Caribbean 52 (55) 56666-333

The Netherlands +31 (0) 23 569 5555

Norway +47 22 07 07 00

People's Republic of China 86 (10) 6235 1230

Poland +48 (0) 22 521 53 40

Republic of Korea 82 (2) 528-5299

Russia, CIS & The Baltics +358 (9) 4783 400

South Africa +27 11 254 8360

Spain +34 (901) 988 054

Sweden +46 8 477 6503/4

Taiwan 886 (2) 2722-9622

United Kingdom & Eire +44 (0) 1344 392400

USA 1 (800) 426-2200

USA (Export Sales) 1 (503) 627-1916

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Updated 13 August 2004

Our most up-to-date product information is available at:
www.tektronix.com



Product Area Assessed: The planning, design/development and manufacture of electronic Test and Measurement instruments.

Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.

Copyright © 2004, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

08/04 DV/WOW

76W-12019-4