

AC/DC Current Probes

TCP0020, TCP2020, TCP202A Datasheet



Features & benefits

- Easy-to-use and accurate AC/DC current measurements
- DC to >50 MHz bandwidth
- Core jaw diameter of 5 mm (0.2 in.)
- Accurately measures current levels as low as 10 mA per division
- High accuracy with typically less than 1% DC gain error
- Split-core construction allows easy circuit connection
- Low noise and DC drift
- TCP0020
 - 20 A_{RMS} maximum current capability
 - 100 A peak pulse current capability
 - Connects directly to oscilloscopes with the TekVPI™ probe interface
 - Provides automatic units scaling and readout on the oscilloscope display
 - One-button degauss and AutoZero control for ease of use

- Easy access to scope-displayed probe menu for probe setup control and operating status information
- Remote control capability through TekVPI oscilloscope
- TCP2020
 - 20 A_{RMS} maximum current capability
 - 100 A peak pulse current capability
 - 10 mA/mV sensitivity
 - BNC output connects to most oscilloscopes and other measurement equipment (>100 kΩ termination required)
 - Degauss button and thumbwheel for DC offset adjustment
 - Powered by an AC adapter
- TCP202A
 - 15 A_{DC} + Peak AC maximum current capability
 - 50 A peak pulse current capability
 - Connects directly to oscilloscopes with the TekProbe™ interface
 - Provides automatic units scaling and readout on the oscilloscope display
 - Degauss button and thumbwheel for DC offset adjustment
- Safety Certified

Applications

- Power supplies
- Semiconductor devices
- Electronic ballasts
- Industrial/consumer electronics
- Mobile communications
- Motor drives
- Transportation systems

TCP0020, TCP2020 and TCP202A

The TCP0020, TCP2020, and TCP202A are a family of high-performance, easy-to-use AC/DC current probes designed for use with a variety of oscilloscopes. The TCP0020 is designed for direct connection to oscilloscopes with the TekVPI™ probe interface and the TCP202A is designed for direct connection to oscilloscopes with the TekProbe™ probe interface. The TCP2020 is designed for use with any instrument with BNC inputs and >100 kΩ input termination.

These AC/DC current probes provide sufficient performance to support 50 MHz measurement system bandwidth. The TCP0020 and TCP2020

provide a maximum 20 A_{RMS} measurement range, while the TCP202A provides a maximum 15 A_{DC + Peak AC} measurement range. These probes also provide excellent accuracy to current levels as low as 10 mA, important for meeting today's challenging current measurement needs.

Specifications

All specifications apply to all models unless noted otherwise.

Characteristics

General

Characteristic	Description
Bandwidth	DC to ≥ 50 MHz
Rise time	20 A _{RMS} (TCP0020 and TCP2020) 15 A _{DC + Peak AC} (TCP202A)
Max peak pulse current	100 A (TCP0020 and TCP2020) 50 A (TCP202A)
Maximum sensitivity	10 mA (on oscilloscopes that support 1 mV/div setting)
Max bare-wire voltage	150 V CAT II (300 V CAT II insulated wire)

Typical

Characteristic	Description
DC accuracy	$\pm 1\%$ typical, $\pm 3\%$ warranted
Max amp-second product	1000 A* μ s (TCP0020 and TCP2020) 500 A* μ s (TCP202A)
Insertion impedance	0.036 Ω at 1 MHz 0.117 Ω at 10 MHz 0.54 Ω at 50 MHz
Signal delay	17 ns

Environmental

Characteristic	Description
Temperature	
Operating	0 °C to +50 °C
Non-operating	-40 °C to +75 °C
Humidity	
Operating	5% to 95% RH, tested up to +30 °C (+86 °F) 5% to 85% RH, tested at +30 °C to +50 °C (+86 °F to +122 °F)
Non-operating	5% to 95% RH, tested up to +30 °C (+86 °F) 5% to 85% RH, tested at +30 °C to +75 °C (+86 °F to +167 °F)
Regulatory	
Safety	CSA1010.1:1997, CSA1010.2.032-96, IEC61010-1:2001, IEC61010-2-032

Physical characteristics

Probe head size	mm	in.
Height	30.5	1.2
Width	15.2	0.6
Length	148	5.8
Cable length	2	79
Weight	kg	lb.
Probe only	0.227	0.5
Shipping	1.22	2 lb. 11 oz.

Power requirements

TCP0020 is powered directly by oscilloscopes with the TekVPI™ probe interface.

TCP2020 is powered by AC adapter. (Specify power plug option when ordering.)

TCP202A is powered directly by oscilloscopes with the TekProbe™ probe interface or through the TekVPI™ probe interface when used with the TPA-BNC adapter.

Standard warranty

One-year parts and labor.

Ordering information

TCP0020	AC/DC current probe. Includes: Instruction manual (English) (071-3002-xx), Probe ground lead – 6 in. length (196-3120-xx), Nylon carrying case (016-1952-xx).
TCP2020	AC/DC current probe. Includes: Instruction manual (English) (071-3002-xx), Probe ground lead – 6 in. length (196-3120-xx), Nylon carrying case (016-1952-xx), AC adapter (specify power plug option when ordering).
TCP202A	AC/DC current probe. Includes: Instruction manual (English) (071-3002-xx), Probe ground lead – 6 in. length (196-3120-xx), Nylon carrying case (016-1952-xx).

Power Plug Options (TCP2020 Only)

Option	Description
Opt. A0	North America Power, 115 V, 60 Hz
Opt. A1	Universal Euro Power, 220 V, 50 Hz
Opt. A2	United Kingdom Power, 240 V, 50 Hz
Opt. A3	Australia Power, 240 V, 50 Hz
Opt. A5	Switzerland Power, 220 V, 50 Hz
Opt. A6	Japan Power, 100 V, 110/120 V, 60 Hz
Opt. A10	China Power, 50 Hz
Opt. A11	India Power, 50 Hz
Opt. A12	Brazil Power, 60 Hz
Opt. A99	No Power Cord

Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. CA1	Single Calibration or Functional Verification
Opt. D1	Calibration Data Report
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. G3	Complete Care 3 Years (includes loaner, scheduled calibration, and more)
Opt. G5	Complete Care 5 Years (includes loaner, scheduled calibration, and more)
Opt. IF	Upgrade Installation Service
Opt. R3	Repair Service 3 Years (including warranty)
Opt. R3DW	Repair Service Coverage 3 Years (includes product warranty period). 3-year period starts at time of instrument purchase
Opt. R5	Repair Service 5 Years (including warranty)
Opt. R5DW	Repair Service Coverage 5 Years (includes product warranty period). 5-year period starts at time of instrument purchase

Opt. S1	On-site Service 1 Year
Opt. S3	On-site Service 3 Years (with R or C options)
Opt. SILV100	Standard warranty extended to 5 years
Opt. SILV200	Standard warranty extended to 5 years
Opt. SILV400	Standard warranty extended to 5 years
Opt. SILV600	Standard warranty extended to 5 years
Opt. SILV900	Standard warranty extended to 5 years

Probes and accessories are not covered by the oscilloscope warranty and Service Offerings. Refer to the datasheet of each probe and accessory model for its unique warranty and calibration terms.

Recommended accessories

Accessory	Description
067-2396-xx	Current loop, 1 turn, 50 Ω with BNC connector used for performance verification
067-1686-xx	Deskew/calibration fixture



Tektronix is ISO 14001:2015 and ISO 9001:2015 certified by DEKRA.

ASEAN / Australasia (65) 6356 3900
 Belgium 00800 2255 4835*
 Central East Europe and the Baltics +41 52 675 3777
 Finland +41 52 675 3777
 Hong Kong 400 820 5835
 Japan 81 (120) 441 046
 Middle East, Asia, and North Africa +41 52 675 3777
 People's Republic of China 400 820 5835
 Republic of Korea +822 6917 5084, 822 6917 5080
 Spain 00800 2255 4835*
 Taiwan 886 (2) 2656 6688

Austria 00800 2255 4835*
 Brazil +55 (11) 3759 7627
 Central Europe & Greece +41 52 675 3777
 France 00800 2255 4835*
 India 000 800 650 1835
 Luxembourg +41 52 675 3777
 The Netherlands 00800 2255 4835*
 Poland +41 52 675 3777
 Russia & CIS +7 (495) 6647564
 Sweden 00800 2255 4835*
 United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
 Canada 1 800 833 9200
 Denmark +45 80 88 1401
 Germany 00800 2255 4835*
 Italy 00800 2255 4835*
 Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
 Norway 800 16098
 Portugal 80 08 12370
 South Africa +41 52 675 3777
 Switzerland 00800 2255 4835*
 USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

25 Jan 2023 51W-28098-1
www.tek.com

Tektronix[®]